

# PERIMOUSSE

## PROPERTIES

**PERIMOUSSE** is an **aqueous phase** product aimed at **destroying all kinds of mosses, lichens, fungi** that grow on **roofs, terraces, facades...**

**PERIMOUSSE** can be sprayed on all types of **tiles and slates** as well as on most construction material.

**PERIMOUSSE** can also be used as a **preventive treatment** for **parasitic plant species decontamination** on facades before any thin paint coating (**DTU 59.1\*** for paint works). As the active molecules penetrate and impregnate the surface treated, micro-organisms' **germination becomes impossible** (for a 2 to 5-year period).

**PERIMOUSSE** is extremely efficient **against red stains** (fungi) on facade renderings. (**CSTB 2669** of 2 August 93).

**PERIMOUSSE** contains no aggressive agent for the surface to be treated.

## INSTRUCTIONS FOR USE

Dilute **1 L** of **PERIMOUSSE** in **4 L water**.

**Damp-spray** or hose the surface before spraying or brushing the product **from BOTTOM TO TOP** until saturation.

**PRECAUTION** : Using chlorine will invalidate **PERIMOUSSE's** action.

When treating roof covers, be extra careful, surfaces that have just been prayed are **extremely slippery**.

**CONSUMPTION** : **1 L** is enough **3 to 4 M2**.

*Mosses and lichens will be eradicated. They will disappear within a month or more thanks to rainfalls. This moss killer remains active up to one year after application. For a faster result, brush and rinse the treated surfaces 48 hours after spraying*

For further information, refer to data sheet.

- NF standard P 74-201-1 (Oct 94)\*

## SAFETY PRECAUTIONS

R22 : Toxic if ingested.

R34 : Causes burns.

S2 : Corrosive. Keep away from children.

S26 : In case of contact with eyes, rinse immediately and thoroughly with water and soap.

S28 : After skin contact, rinse immediately with water and soap.

*Produit à usage strictement professionnel.*

*Eviter absolument le contact ou le mélange avec d'autres produit chimiques.*

*Fiche de Sécurité sur Minitel au 08 36 05 10 12.*

**Cette fiche technique annule et remplace toutes les précédentes concernant ce produit . (Octobre 2000)**

Les informations contenues dans la présente notice sont l'expression de nos connaissances et des résultats d'essais effectués dans un souci constant d'objectivité. Elles ne peuvent cependant en aucun cas être considérées comme apportant une garantie ni comme engageant notre responsabilité en cas d'application défectueuse, puisque la manipulation et la mise en œuvre de notre produit échappe à notre contrôle. Il appartient à l'utilisateur de s'assurer par des essais préalables que le produit convient parfaitement à l'usage auquel il le destine. Notre garantie ne saurait excéder le remplacement d'un produit reconnu défectueux dans un délai d'une année après sa livraison

18/07/07